



**POLIMASTER**<sup>®</sup>  
Radiation Detection Technologies



# MULTIPURPOSE HAND-HELD RADIATION MONITOR/IDENTIFIER PM1401K-3PM

**PM1401K-3PM is designed for detection and localization of radioactive materials by registration of photon (gamma and X-ray) and neutron radiation. The device can accumulate gamma spectra, identify radioactive isotopes, measure photon dose equivalent and dose equivalent rate.**

This is the smallest and the most lightweight instrument in the world which is capable to operate simultaneously as an alarming device, search instrument, spectrometer and identifier.

Bright color LCD and intuitive menu make the device easy to use.

The gamma and neutron detectors are built into a lightweight and compact case.

Shock and water resistant case ensures protection class IP65.

PM1401K-3PM is equipped with Bluetooth and GPS modules.

## Applications

- Customs and border control
- Radiological and isotope laboratories
- Emergency services
- First responders
- Police and security
- Various industry branches where nuclear technical units and ionizing radiation sources are used

## Features

Detection, search and localization of gamma, X-ray and neutron radiation sources

Precise dose and dose rate measurement

Audible, visual and vibration alarms

Designed to comply with ANSI N42.34, IEC 62327, ANSI N42.42

Recording and storage of not less than 10 000 events and 1 000 gamma spectra

Sending the accumulated spectra to a PC via USB or Bluetooth

Built-in GPS



## Specifications

The instrument is designed to comply with the requirements of ANSI N42.34-2015, IEC 62327:2017, ANSI N42.42-2012

### GAMMA SEARCH, SPECTROMETRIC CHANNEL

Detector	CsI(Tl)
Sensitivity <sup>137</sup> Cs, no less than <sup>241</sup> Am, no less than <sup>60</sup> Co, no less than	400 (cps)/(μSv/h) or 4 (cps)/(μrem/h) 4000 (cps)/(μSv/h) or 40 (cps)/(μrem/h) 200 (cps)/(μSv/h) or 2 (cps)/(μrem/h)
Gamma radiation scintillation spectra acquisition channels	1024
Full width at half maximum (FWHM) for <sup>137</sup> Cs	from 6.5 % to 8.0 %
Maximum quantity of scintillation spectra saved in the instrument memory	up to 1000
Relative intrinsic error of transformation characteristic (integral nonlinearity) when acquiring scintillation spectra	≤ 1.0 %

### NEUTRON SEARCH CHANNEL

Detector	LiF/ZnS
Energy range	from thermal (0.025x10 <sup>-6</sup> MeV) to 14 MeV
Sensitivity to neutron radiation - Pu-α-Be - thermal neutrons	0.15 cps·cm <sup>2</sup> 5.0 cps·cm <sup>2</sup>

### GAMMA MEASUREMENT CHANNEL

Detector	GM-counter
Dose equivalent rate (DER) measurement range	0.01 μSv/h - 15 mSv/h (1 μrem/h - 1.5 rem/h)
Accuracy of DER measurement <sup>137</sup> Cs: 0.01 - 1 μSv/h (1 - 100 μrem/h) <sup>137</sup> Cs: 1 μSv/h - 15 mSv/h (100 μrem/h - 1.5 rem/h) <sup>241</sup> Am <sup>60</sup> Co	± 30 % ± 10 % ± 30 % ± 30 %
Dose equivalent (DE) indication range	0.1 μSv - 1 Sv (10 μrem - 100 rem)
Energy range	0.025 - 15 MeV

### GENERAL

Alarms	visual, audible, external vibration
Data transfer communication channels	USB, Bluetooth
Battery lifetime	≥ 210 h
Battery	2 x AA
Protection degree	IP65
Weight of the instrument with batteries	≤ 0.90 kg (2 lb)
Dimensions	262x60x65 mm



Quality management system  
ISO 9001

- Customer focus
- Customer satisfaction
- Continuous improvement
- System/process effectiveness

ID 15 100 148764

www.tuev-thueringen.de

#### North America

Polimaster Inc.  
44873 Falcon Place, Suite 128  
Sterling, VA 20166, USA  
Phone: +1 703 525 5075  
Fax: +1 703 525 5079  
info@polimaster.us  
[www.polimaster.us](http://www.polimaster.us)

#### Europe

Polimaster Europe UAB  
Ezero g. 4, Didziasalio k.  
Nemezio sen., Vilnius r.  
LT-13264 Republic of Lithuania  
phone: +370 5 210 2323  
fax: +370 5 210 2324  
polimaster@polimaster.eu  
[www.polimaster.eu](http://www.polimaster.eu)

#### Asia, Africa, Latin America, Australia and Oceania

Polimaster Ltd.  
51, Skoriny St., Minsk  
220141 Republic of Belarus  
phone: +375 17 3963675, +375 17 2686819  
fax: +375 17 264 2356  
polimaster@polimaster.com  
[www.polimaster.com](http://www.polimaster.com)

#### Japan

Polimaster Japan Co., Ltd.  
AUBE2 5-177 Kuratsuki  
Kanazawa, Ishikawa Prefecture  
920-8203 Japan  
phone: + 81 076 201 8623  
fax: + 81 076 201 8624  
pacific@polimaster.jp  
[www.polimaster.jp](http://www.polimaster.jp)